



PRODUCT DATA SHEET –PTI ADDITIVES

NO PEEL™ **PT-900**

DESCRIPTION

NO PEEL – PT-900 is formulated to enable epoxy and polyurethane topcoats flow evenly despite certain surface defects or contaminants. This additive helps prevent “Orange Peel”—the pitting in paint caused by contaminants on the substrate’s surface or in the spray gun. **NO PEEL™** is flow additive.

APPLICATION

Add a 4 oz. bottle to 1 gallon of component A material only. Do not add to Comp B (catalyst) material. This is approximately 4% by volume. If material still is not flowing properly, another 4 oz. bottle may be added. Do not add more than 8 total ounces of additive as it may adversely affect the quality of the cured topcoat. Mix **THOROUGHLY** by hand, mechanical mixer, or with a shaker.

HEALTH, SAFETY, & STORAGE REQUIREMENTS

Refer to each individual material SDS (Safety Data Sheet) for specific requirements on the health, safety, storage and handling requirements. Follow all local, state, and national regulations during surface preparation, material application and cleanup.

PRODUCT INFORMATION & DISCLAIMER

Product Data Sheets are periodically updated to reflect new information. It is important to use the latest and most recent revision for the product being used. The foregoing information is accurate to the best of our knowledge. However, due to differences in customer handling, use and method of application which are not known and are beyond our control, Products Techniques, Inc. makes no warranties as to the end result.