



## PRODUCT DATA SHEET –PTI ADDITIVES

### NO POP™

#### DESCRIPTION

**NO POP™** is a specially formulated additive. When paint is applied, particularly by spraying, the solvents that carry the resin and the pigments “flash off” – evaporate. This product is used to slow that process particularly in hot and humid weather. This allows the paint to flow evenly and prevents a condition known as “solvent pop”—the formation of small air bubbles on the surface of the paint. It also prevents a condition known as “dry spray”—solvent evaporating before the paint hits the surface of the substrate. So, **NO POP™** keeps the material wet allowing it to flow, dry, and cure as it should.

#### SOLVENT PROPERTIES & CHARACTERISTICS

Flash Point	230° F
Weight (lbs per gallon)	7.92 lbs
Color	Clear
Volatile Organic Compounds (VOC)	950 g/l

#### SHELF LIFE

Shelf life is only applicable for materials stored in unopened and undamaged original factory filled containers. 1 year when stored at 50°-85° F

#### USAGE

Add 8 fluid ounces of **NO POP™** to 1 gallon of material or 2 fluid ounces to 1 quart of material. In a 2 component system, always add **NO POP™** to the component A. Mix well. Admix with the Component B as required.

#### HEALTH, SAFETY, & STORAGE REQUIREMENTS

Refer to each individual material SDS (Safety Data Sheet) for specific requirements on the health, safety, storage and handling requirements. Follow all local, state, and national regulations during surface preparation, material application and cleanup.

#### PRODUCT INFORMATION & DISCLAIMER

Product Data Sheets are periodically updated to reflect new information. It is important to use the latest and most recent revision for the product being used. The foregoing information is accurate to the best of our knowledge. However, due to differences in customer handling, use and method of application which are not known and are beyond our control, Products Techniques, Inc. makes no warranties as to the end result.