

PRODUCT DATA SHEET

PTC-2001 CLEANER/DEGREASER PTI CLEANER SERIES

DESCRIPTION

PTC-2001 specifically formulated to be biodegradable, water dilutable and environmentally safe for use on aerospace equipment, aircraft equipment, aircraft exteriors, aerospace/aircraft ground equipment (AGE), AGE Engines and landing gear. PTC-2001 is the only product needed to remove hydraulic fluid, jet exhaust and other difficult to remove dirt and grime from aircraft. PTC-2001 is non-caustic, biodegradable, doesn't contain any solvents or HAPS (Hazardous Air Pollutants). PTC-2001 exceeds all U.S., Japanese and European Community VOC standards.

CLEANER PROPERTIES & CHARACTERISTICS

Odor	None
PH	6-8
Flammable	Non-Flammable
Biodegradable	Yes
Weight (Pounds per gallon)	8.9 lbs
Solvents	No organic or inorganic solvents
Carcinogenic	No
Hazardous Air Pollutants	None
VOC	0 g/l
Specifications	Boeing D6-17487 Rev P, Douglas Aircraft CSD No. 1 TYI, Mil -PRF 87937D Type II & Type IV, & AMS 1526B

SHELF LIFE

Shelf life is only applicable for materials stored in unopened and undamaged original factory filled containers. 1 year when stored between 50°-85° Fahrenheit.

MIXING/APPLICATION INSTRUCTIONS

- Do not mix with other products. A harmful reaction may occur.
- Dilute with water prior to use. For Heavy degreasing mix 3:1 with water. For light duty cleaning mix up to 40:1 with water. To clean windows (glass or plastic) dilute 80-90 parts water to 1 part concentrate. **THIS IS THE ONLY CLEANER /DEGREASER YOU WILL EVER NEED. SIMPLY ADJUST THE DILUTION RATIO TO SUIT THE JOB.**
- For pressure washer and steam cleaner use, dilute a minimum of 10:1 with water.
- Spray product onto aircraft.
- Scrub with a soft brush, sponge or wash mitt
- Rinse with de-ionized water to prevent spotting.

NOTE: Application of PTI products requires the use of all OSHA approved safety equipment, including proper ventilation. Additionally, PTI products require the recommended temperature/humidity conditions and film thickness ranges for optimal performance. The material, hangar, and aircraft skin temperatures should be no lower than 75° F / 25° C before, during and after application.

HEALTH, SAFETY, & STORAGE REQUIREMENTS

Refer to each individual material SDS (Safety Data Sheet) for specific requirements on the health, safety, storage and handling requirements. Follow all local, state, and national regulations during surface preparation, material application and cleanup.

PRODUCT INFORMATION & DISCLAIMER

Product Data Sheets are periodically updated to reflect new information. It is important to use the latest and most recent revision for the product being used. The foregoing information is accurate to the best of our knowledge. However, due to differences in customer handling, use and method of application which are not known and are beyond our control, Products Techniques, Inc. makes no warranties as to the end result.