

PRODUCTS TECHNIQUES, INC.

Safety Data Sheet

SECTION 1 - PRODUCT & COMPANY INFORMATION

Product Name: POLYURETHANE CATALYST FOR ALL GLOSS LEVELS Product Code: PT-799-CATALYST

Products/Techniques, Inc.
3271 S. Riverside Ave.
Bloomington, CA 92316

PH: 909.877.3951
FX: 909.877.6078
E-mail: pti@ptipaint.com
Web: www.ptipaint.com

CHEMTREC: 1.800.424.9300

OPERATING HOURS: 8:00 am - 4:30 pm PDT

SECTION 2 - HAZARDS IDENTIFICATION

HMIS:230X

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Oral Toxicity	Acute Tox. 4	Oral>300+<=2000mg/kg
Dermal Toxicity	Acute Tox. 4	Dermal>1000+<=2000mg/kg
Inhalation Toxicity	Acute Tox. 4	Gases>2500+<=5000ppm, Vapors>10+<=20mg/l, Dusts&mists>1+<=5mg/l
Skin corrosive	3	Reversible adverse effects in dermal tissue, Draize score: >= 1.5 < 2.3
Eye corrosive	2B	Mild eye irritant: Subcategory 2B, Reversible in 7 days
Respiratory sensitizer	1B	Respiratory sensitizer
Skin sensitizer	1B	Skin sensitizer
Carcinogen	2	Limited evidence of human or animal carcinogenicity

GHS Hazards

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H305	May be harmful if swallowed and enters airways
H313	May be harmful in contact with skin
H316	Causes mild skin irritation
H317	May cause an allergic skin reaction
H320	Causes eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H350	May cause cancer

GHS Precautions

P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/.../equipment

P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P262	Do not get in eyes, on skin, or on clothing
P264	Wash ... thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P280	Wear protective gloves/protective clothing/eye protection/face protection
P310	Immediately call a POISON CENTER or doctor/physician
P322	Specific measures (see ... on this label)
P361	Remove/Take off immediately all contaminated clothing
P363	Wash contaminated clothing before reuse
P302+P350	IF ON SKIN: Gently wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P332+P313	If skin irritation occurs: Get medical advice/attention
P370+P378	In case of fire: Use ... for extinction
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container to ...

Signal Word: Danger



SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
PARACHLOROBENZOTRIFLOURIDE	98-56-6	58.53%
HEXANE, 1,6-DIISOCYANATO-, HOMOPOLYMER	28182-81-2	29.25%
1-METHOXY-2-PROPANOL ACETATE	108-65-6	7.41%
HEPTAN-2-ONE	110-43-0	2.85%
2-(2-BUTOXYETHOXY) ETHANOL	112-34-5	1.04%
BENZENESULFONYLISOCYANTE, 4-METHYL-	4083-64-1	0.90%

SECTION 4 - FIRST AID MEASURES

INHALATION: If breathing problems occur during use, **LEAVE AREA IMMEDIATELY** and get fresh air. If breathing problems remain, **SEEK IMMEDIATE MEDICAL ATTENTION.**

EYE CONTACT: Flush eyes with large amounts of clean water for at least 20 minutes. Seek immediate medical attention.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and launder before re-use.

INGESTION: Do not induce vomiting. Get immediate medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 0 C (32 F)

LEL: 1.00

UEL: 25.00

All flashpoints: TCC

EXTINGUISHING MEDIA: Alcohol foam, carbon dioxide (CO₂), dry chemical, water spray/water fog extinguishing systems

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back. Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 - HANDLING & STORAGE

HANDLING: Wear all appropriate Personal Protective Equipment (PPE). Wear appropriate respiratory protection and ensure adequate ventilation at all times as vapors can accumulate over time in enclosed spaces and poorly ventilated areas. Use product in a way that minimizes splashes and/or creation of dust. Wash with soap and water thoroughly after each use.

STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use. Store in a cool dry area at a temperature between 50 and 95 degrees F. Do not store outside in direct sunlight.

SECTION 8 - EXPOSURE CONTROL AND PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
PARACHLOROBENZOTRIFL OURIDE 98-56-6	Not Established	Not Established	Not Established
HEXANE, 1,6- DIISOCYANATO-, HOMOPOLYMER 28182-81-2	Not Established	Not Established	Bayer: 0.5 mg/m ³ TWA STEL 1.0 mg/m ³ (15 min)
1-METHOXY-2-PROPANOL ACETATE 108-65-6	TWA 50 PPM	Not Established	Not Established
HEPTAN-2-ONE 110-43-0	100 ppm TWA; 465 mg/m ³ TWA	50 ppm TWA	NIOSH: 100 ppm TWA; 465 mg/m ³ TWA
2-(2-BUTOXYETHOXY) ETHANOL 112-34-5	TWA 20ppm TWA 50ppm 240mg/m ³	Not Established	Not Established

BENZENESULFONYLISOCY ANTE, 4-METHYL-4083-64-1	Not Established	Not Established	Not Established
---	-----------------	-----------------	-----------------

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

VENTILATION & RESPIRATORY PROTECTION: Always follow all local, state, and federal laws and regulations regarding the use of respirators. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Wear a MSHA/NIOSH approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

ADMINISTRATIVE CONTROLS: All individual company safety policies should be reviewed to determine compliance with applicable Federal, State and local safety regulations. If a company determines that threshold limit values and air quality contaminant level have not been exceeded, then that company should set it's own policies regarding the use of respirators and other Personal Protective Equipment.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, such as neoprene or solvent resistant nitrile. To prevent repeated or prolonged skin contact, wear impervious clothing such as a chemical suit, rubber boots, and/or chemical safety goggles plus a face shield if such should be necessary. If the equipment to be worn is not available or the type of equipment for a specific job is not known, consult a reputable safety equipment supply company. Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

This product exhibits the following properties under normal conditions:

<p>Appearance Clear liquid</p> <p>Physical State Liquid</p> <p>Vapor Pressure 6.7 X 10⁻⁶ @ 68F</p> <p>Wt% Solids 30.16</p>	<p>Odor Solvent like</p> <p>Vapor Density 4.49</p> <p>Boiling Range 125 to 230 °C, 257 to 446 °F</p> <p>Weight/Gallon 10.07</p>
---	---

VOC(g/l) Less H2O and Exempt Compounds VOC (g/L) Material 136.44 % VOC (C.A.R.B) 11.31	VOC(lbs/gal) Less H2O and Exempt Compounds 2.40 Specific Gravity 1.21
---	--

SECTION 10 - REACTIVITY & STABILITY

STABILITY:

STABLE

INCOMPATIBILITY (Materials to avoid): strong acids and bases, oxidizers, and selected amines.

CONDITIONS TO AVOID: Avoid all possible sources of ignition.

No Data

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide (CO) and carbon dioxide (CO2). Other unknown hazardous products are possible.

No Data

Hazardous polymerization will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Mixture Toxicity

Dermal Toxicity LD50: 3mg/kg
Inhalation Toxicity LC50: 20mg/L

Component Toxicity

- 98-56-6 PARACHLOROBENZOTRIFLOURIDE
Oral LD50: 13 g/kg (Rat) Dermal LD50: 2 mg/kg (Rabbit:) Inhalation LC50: 33 mg/L (Rat)

- 28182-81-2 HEXANE, 1,6-DIISOCYANATO-, HOMOPOLYMER
Oral LD50: 5,000 mg/kg (Rat)

- 110-43-0 HEPTAN-2-ONE
Oral LD50: 1,670 mg/kg (Rat)

- 112-34-5 2-(2-BUTOXYETHOXY) ETHANOL
Oral LD50: 3,384 mg/kg (Rat) Dermal LD50: 2,700 mg/kg (Rabbit)

- 4083-64-1 BENZENESULFONYLISOCYANTE, 4-METHYL-
Oral LD50: 2,234 mg/kg (Rat) Inhalation LC50: 640 ppm (Rat:)

INHALATION: Headaches, dizziness, nausea, decreased blood pressure, change in heart rate, and cyanosis may result from overexposure to vapor. **Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.**

INGESTION: This material may be harmful or fatal if swallowed.

SKIN CONTACT: May cause sensitization or allergic reaction.

EYE CONTACT: Direct contact with liquid, exposure to vapors or mist may cause stinging, tearing, redness, swelling and eye damage.

Routes of Entry:

Inhalation Skin Contact Eye Contact Ingestion

Exposure to this material may affect the following organs:

Effects of Overexposure

CARCINOGENICITY:

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
None			No Data

ACUTE TOXICITY:

INHALATION: Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

CONDITIONS AGGRAVATED: Unknown.

CHRONIC EFFECTS: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.

SECTION 12 - ECOLOGICAL INFORMATION

No information available.

Component Ecotoxicity

PARACHLOROBENZOTRIFLOURIDE	48 Hr LC50 Lepomis macrochirus: 11.5-15.8 mg/L [static] 48 Hr EC50 Daphnia magna: 3.68 mg/L
HEXANE, 1,6-DIISOCYANATO-, HOMOPOLYMER	ACUTE AND PROLONGED TOXICITY TO FISH: Zebra fish/LC50 (96 h): > 100 MG/L ACUTE TOXICITY TO AQUATIC INVERTEBRATES: Daphnia magna/EC50: > 100 mg/l TOXICITY TO MICROORGANISMS: Bacteria/EC50 (3 h): > 1,000 mg/l
1-METHOXY-2-PROPANOL ACETATE	96 Hr LC50 Pimephales promelas: 161 mg/L [static] 48 Hr EC50 Daphnia magna: >500 mg/L
HEPTAN-2-ONE	96 Hr LC50 Pimephales promelas: 131.0 mg/L [flow-through]
2-(2-BUTOXYETHOXY) ETHANOL	96 Hr LC50 Lepomis macrochirus: 1300 mg/L [static] 24 Hr EC50 water flea: 2850 mg/L; 48 Hr EC50 Daphnia magna: >100 mg/L 96 Hr EC50 Scenedesmus subspicatus: >100 mg/L
BENZENESULFONYLISOCYANATE, 4-METHYL-	TOXICITY TO ALGAE EC50: 23 mg/L Selenastrum capricornutum 72 h (p-Toluene sulfonamide 70-55-3) TOXICITY TO FISH LC50: 435 mg/L Oryzias latipes 96 h (p-Toluene sulfonamide 70-55-3) DAPHNIA MAGNA (WATER FLEA) EC50: 150 mg/L Daphnia magna 72 h (p-Toluene sulfonamide 70-55-3)

SECTION 13 - DISPOSAL CONSIDERATIONS

It is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition. Maximize material recovery for reuse or recycling.

It is the responsibility of the user to determine if the material is a RCRA "hazardous waste" at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more restrictive. Contact your regional US EPA office for guidance concerning case specific disposal issues.

Non-usable product is regulated by US EPA as hazardous material under the following codes:

SECTION 14 - TRANSPORTATION / SHIPPING INFORMATION

Hazardous Material! Ship according to all applicable local, state, and federal regulations regarding labeling and packaging requirements.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
D.O.T.	PAINT	UN 1263	II	3
IATA	PAINT	UN 1263	II	3
IMO	PAINT	UN 1263	II	3

SECTION 15 - REGULATORY INFORMATION

Additional regulatory listings, where applicable.

The following chemicals are listed under California Proposition 65:

- None

The following chemicals appear on the New Jersey Right-To-Know Chemicals list:

108-65-6 1-METHOXY-2-PROPANOL ACETATE
110-43-0 HEPTAN-2-ONE

The following chemicals appear on the Pennsylvania Right-To-Know list:

108-65-6 1-METHOXY-2-PROPANOL ACETATE 7.41 %
110-43-0 HEPTAN-2-ONE 2.85 %

SARA HAZARD CATEGORY: The product has been reviewed according to the EPA 'Hazard Categories' promulgated under sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

98-56-6 PARACHLOROBENZOTRIFLOURIDE Fire Hazard, Chronic Health Hazard
108-65-6 1-METHOXY-2-PROPANOL ACETATE Fire Hazard, Acute Health Hazard
110-43-0 HEPTAN-2-ONE Fire Hazard
112-34-5 2-(2-BUTOXYETHOXY) ETHANOL Acute Health Hazard, Chronic Health Hazard

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

HEXANE, 1,6-DIISOCYANATO-, HOMOPOLYMER 29.25 %

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
----------------	-------------------	------------------------------

EU Risk Phrases

Safety Phrase

The chemical substances listed below are not on the TSCA Section 8 Inventory:

- None

SARA Section 313: The product contains the following substances subject to the reporting requirements of section 313 and Title II of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

SECTION 16 - OTHER INFORMATION

The information in this document is believed to be correct as of the date printed.

NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT OF THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.


(C) Copyright, 2013 Products Techniques, Inc.

Hazardous Material Information System (HMIS)

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

HMIS & NFPA Hazard Rating Legend
* = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE
3 = HIGH

National Fire Protection Association (NFPA)



Reviewer Revision

Date Prepared: 4/23/2018